


		Shank	OAL	Order Number			
Tip Thck.	Tip Lngth.			HNT Carbide	List Price	HNT Carbide Max	List Price
Inch							
0.024	0.1	,125	2.5				
0.024	0.2	0.25	2.5			SPTB-M-2422525	Contact Allomet
0.024	0.3	0.375	2.5			SPTB-M-2433725	Contact Allomet
0.024	0.4	0.5	4			SPTB-M-2445040	Contact Allomet
Metric							
0.61	3.2	4	42				
0.61	4.8	6	70			SPTB-M-6148670	Contact Allomet
0.61	6.4	8	75			SPTB-M-6164875	Contact Allomet
0.61	8.0	10	95			SPTB-M-61801095	Contact Allomet

Allomet Single Point Tool Blanks are produced utilizing high-value powdered metal wafers brazed to the tip of the rod. The powder is produced from a patented and proprietary powder metal production method known as "Tough-Coated Hard Powder (TCHP)" process technology. The TCHP process results in strength, durability and wear resistance properties never attainable with carbide tools. Allomet's unique family of cutting tools, tool blanks and disks are produced using the TCHP process, resulting in "Hard 'N Tough" cutting tool material - increased hardness without sacrificing toughness. These products are branded as EternAloy HNT.



EternAloy[®] Hard 'N Tough.....Taking Wear Resistance to the Extreme.'



509 Hahntown-Wendel Road North Huntingdon, PA 15642 TEL: (724) 864-4787 FAX: (724) 864-4562 sales@Allomet.com

www.allomet.com

